MARTCARE® 1011 DISPOSABLE MASKS MOULDED FFP1 - VALVED

PRODUCT CODE: BEH110-001-00

THE FFP1V IS A TRADITIONALLY DESIGNED MASK WITH VALVE FOR FINE NON-TOXIC DUSTS, FIBRES AND MISTS

TECHNICAL SPECIFICATION

MARTCARE® RANGE

INSTRUCTIONS FOR USE

Mask must be fitted in accordance with the instructions supplied

Care must be taken to ensure that the correct mask type is selected for the work to be carried out

If in doubt as to the type of mask required seek professional advice

MATERIALS

Man made fibres C/W Aluminium Nose Piece and Rubber Straps Polystyrene exhalation valve C/W rubber diaphragm (if applicable)

PERFORMANCE

Offers an assigned protection factor (APF) of 4 x Workplace Exposure Limit (WEL) for dusts, fibres, fumes and mists

DIMENSIONS OF OUTER PACKAGING

Quantity: 100

Height: 217mm

Width: 278mm

Length: 655mm

Weight: 2.45Kg (Approx.)

CLEANING & MAINTENANCE

Not applicable - disposable product

Store the masks out of direct sunlight away from chemicals and in a dry atmosphere

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jspsafety.com



DIMENSIONS OF MASK

Height: 150mm

Width: 13mm

Length: 132mm

Weight: 13g (Approx.)

LIMITATIONS OF USE

Protection will only be offered if the mask is fitted correctly

The mask, when in contact with the skin may cause allergic reactions to susceptible individuals

If this occurs leave the hazard area, remove mask and seek medical advice

Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres

The mask must be discarded and replaced if it is:

- a.) Removed whilst in the contaminated area,
- b.) Breathing difficulties due to clogging are experienced or,
- c.) The mask becomes damaged

This mask is not designed to be worn by people with facial hair

CONFORMITY

Meets the FFP1 requirements of EN 149

CE Certificate Number 701950, issued by BSi Product Certification

















