

MARTCARE® 1231 DISPOSABLE MASK

MOULDED, VALVED - FFP3

TECHNICAL SPECIFICATION

PRODUCT CODE: BEH130-001-00

FFP3 VALVED MASK MINIMISES BREATHING RESISTANCE AND MAXIMISES THE DUST CARRYING CAPACITY, PROTECTION FROM FINE DUSTS, FUMES AND FIBRES AND AQUEOUS MISTS

MARTCARE® RANGE

INSTRUCTIONS FOR USE

Mask must be fitted in accordance with the instructions supplied

Care must be taken to ensure that the correct mask type is selected for the work to be carried out

If in doubt as to the type of mask required seek professional advice



MATERIALS

Man made fibres C/W Aluminium Nose Piece and Rubber Straps (latex free) Polystyrene exhalation valve C/W rubber diaphragm (if applicable)

DIMENSIONS OF MASK

Height: 131mm

Width: 65mm

Length: 210mm

Weight: 23g (Approx.)

PERFORMANCE

Offers an assigned protection factor (APF) of 20 x Workplace Exposure Limit (WEL) for very fine dusts, fibres, fumes and mists

DIMENSIONS OF OUTER PACKAGING

Quantity: 50

Height: 218mm

Width: 320mm

Length: 698mm

Weight: 2.72Kg (Approx.)

LIMITATIONS OF USE

Protection will only be offered if the mask is fitted correctly

The mask, when in contact with the skin may cause allergic reactions to susceptible individuals

If this occurs leave the hazard area, remove mask and seek medical advice

Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres

The mask must be discarded and replaced if it is:

- Removed whilst in the contaminated area,
- Breathing difficulties due to clogging are experienced or,
- The mask becomes damaged

This mask is not designed to be worn by people with facial hair or other facial features that may affect seal performance

CLEANING & MAINTENANCE

Not applicable - disposable product

Store the masks out of direct sunlight away from chemicals and in a dry atmosphere

CONFORMITY

Meets the FFP3 requirements of EN 149:2001 + A1:2009

CE Certificate Number 701950, issued by BSI Product Certification

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jpsafety.com



MANUFACTURING FOR SAFETY
WWW.JSPSAFETY.COM

UKSALES@JSPSAFETY.COM
TEL: +44 (0)1993 826050

