

PS 29 F ACT Wide belts with paper backing for Wood



Applications

Wood

Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Open
Backing	F-paper

PS 29 F ACT wide belts with a paper backing for work on wood

The PS 29 F ACT is used for calibration and finish sanding in combination with a pressure pad – these types of applications require a finer grit size. This abrasive paper comes with an **open coating** and is antistatic. These characteristics combined with the bonding agent formulated from Klingspor's ACT recipe add up to outstanding stock removal, phenomenal service life and minimal clogging thanks to the **antistatic** properties. The product's main fields of application are the

- sanding of **softwood**
- processing of plastic
- removal of fillers from surfaces

PS 29 F ACT is generally manufactured with an F1-type lap joint. This means that the lap joint is cut with a bevel and joined with an overlap. This manufacturing process ensures smooth operation all around - including at the joint of the belt.

Uniform scratch pattern over a long period of time

The Klingspor **wide belt** PS 29 F ACT produces an impressively uniform scratch pattern when used for processing surfaces made of softwood. The open coating delivers clean stock removal without premature clogging, while the ACT bonding on F- weight paper provides for the necessary stability. These properties allow the **wide belt** PS 29 F ACT to be used for extended periods without suffering any loss in performance. It holds up even under intense strain and sets itself apart with its outstanding service life.

Handheld machines and stationary devices

The **wide belt** PS 29 F ACT is an equally popular choice for workshops and construction sites and for do-it-yourselfers. While grinding jobs are usually performed on wide belt machines, other dimensions of the belt can be used in combination with belt sanding machines. PS 29 F ACT is available in a wide variety of dimensions. Customers can choose from all standard dimensions common in the industry - in terms of both width and long. The available grit sizes range from extra coarse to medium and fine.

Width in mm	Length in mm	Grit	Belt joint	Type of coated abrasives	Cat.number
1.120	1.900	60	F1 glued overlapped	PS 29 F	292903
1.120	1.900	80	F1 glued overlapped	PS 29 F	292904
1.120	1.900	100	F1 glued overlapped	PS 29 F	292935
1.120	1.900	120	F1 glued overlapped	PS 29 F	292936

1.120	1.900	150	F1 glued overlapped	PS 29 F	292937
1.350	2.620	60	F1 glued overlapped	PS 29 F	292938
1.350	2.620	80	F1 glued overlapped	PS 29 F	292939
1.350	2.620	120	F1 glued overlapped	PS 29 F	292941
1.350	2.620	150	F1 glued overlapped	PS 29 F	292942
930	1.525	80	F1 glued overlapped	PS 29 F	307852
930	1.525	120	F1 glued overlapped	PS 29 F	307854
1.100	1.900	80	F1 glued overlapped	PS 29 F	307857
1.100	1.900	120	F1 glued overlapped	PS 29 F	307859
1.120	2.150	80	F1 glued overlapped	PS 29 F	307863
1.120	2.150	120	F1 glued overlapped	PS 29 F	307865
1.350	2.620	180	F1 glued overlapped	PS 29 F	307867