


Data Sheet



PS 33 CK Discs with paper backing, self-fastening for Paint, Varnish, Filler, Wood



Applications

Paint



Varnish



Filler



Wood



Plastic



Properties

Bonding agent

Resin

Grain

Aluminium oxide

Coating

Semi-open

Backing

C-paper

Abrasive disc PS 33 CK – the versatile abrasive by Klingspor

Devised to work especially well with **random orbital sanders**, the **abrasive disc PS 33 CK** by Klingspor has been equipped with **hook and loop** lamination. Thanks to its dependable hook and loop coating on the back, the disc can be attached by simply pressing it onto the sanding surface of the machine. Thanks to its full-surface attachment, the **abrasive disc** will stay smoothly and firmly in place. Its exceptional qualities make this abrasive the perfect choice for sanding jobs on

- varnish,
- **wood and paint** as well as
- filler.

Klingspor makes these abrasive papers available with different diameters and hole patterns to ensure that they will fit on all common sanders. Better still, the available abrasive discs without holes also offer universal compatibility. However, abrasive papers without holes do not allow for connection to a dust extraction system.

Klingspor abrasive disc with a high removal rate

Klingspor abrasive papers **PS 33 CK** come with an aluminium oxide grain that has been applied with a semi-open coating. Synthetic aluminium oxide is set apart by its great hardness and toughness. These properties allow the **abrasive disc** to deliver a high removal rate and a long service life. Grains composed of aluminium oxide have irregular shapes ranging from wedges to blocks. Thanks to their crystalline characteristics, aluminium oxide abrasives are guaranteed to produce efficient results. The semi-open coating of the grain is ideal for treating surfaces made up of varnish as well as **wood and paint**. This coating creates spaces between the grains that are large enough to allow for an efficient discharge of abrasive debris and dust. This keeps residue from settling between the grains and, as a result, supports a long service life.

Synthetic resin bond on a paper backing (C-paper) for a vast area of applications

The foundation of the **abrasive disc PS 33 CK** by Klingspor is formed by a **paper backing (C-paper)**. The paper used for this backing is of medium weight, making it easy to cut, tear and bend the paper. This flexibility allows the user to bend or tear these abrasive papers and use them for hand sanding wherever **random orbital sander** cannot handle hard-to-reach places. The aluminium oxide grains are bonded to the paper backing with synthetic resin and coated with an extra synthetic resin top size coat. Aside from giving the abrasive paper its colour, this size coat provides additional support against the lateral forces that act on the grain during sanding. The synthetic resin layer coating the grain will automatically wear off at the beginning of sanding and not affect abrasive performance in any way.

Diameter in mm	Grit	Hole pattern	Type of coated abrasives	Cat.number
150	80	hole pattern GLS1	PS 33 CK	143130
150	100	hole pattern GLS1	PS 33 CK	143131
150	80	hole pattern GLS2	PS 33 CK	143132
150	100	hole pattern GLS2	PS 33 CK	143133
150	100	hole pattern GLS3	PS 33 CK	143694
150	80	no hole	PS 33 CK	146739
150	120	no hole	PS 33 CK	146740
150	80	hole pattern GLS3	PS 33 CK	146946
150	120	hole pattern GLS3	PS 33 CK	146947
125	40	hole pattern GLS5	PS 33 CK	146954
115	120	no hole	PS 33 CK	146955
150	40	hole pattern GLS1	PS 33 CK	146978
150	60	hole pattern GLS1	PS 33 CK	146979
150	120	hole pattern GLS1	PS 33 CK	147093
150	100	no hole	PS 33 CK	147106
150	60	no hole	PS 33 CK	147107
150	60	hole pattern GLS3	PS 33 CK	147124
115	80	no hole	PS 33 CK	147144
125	120	hole pattern GLS5	PS 33 CK	147170
150	120	hole pattern GLS2	PS 33 CK	147225
150	60	hole pattern GLS2	PS 33 CK	147226
125	60	no hole	PS 33 CK	147604
125	60	hole pattern GLS5	PS 33 CK	147642
125	80	hole pattern GLS5	PS 33 CK	147643
150	40	hole pattern GLS3	PS 33 CK	147647
115	40	no hole	PS 33 CK	147701
150	40	no hole	PS 33 CK	147922
125	100	hole pattern GLS5	PS 33 CK	147977
115	60	no hole	PS 33 CK	148469
125	80	no hole	PS 33 CK	149055
125	100	no hole	PS 33 CK	150431
125	120	no hole	PS 33 CK	150433
125	40	no hole	PS 33 CK	154113
225	60	no hole	PS 33 CK	210124
225	80	no hole	PS 33 CK	210129
225	120	no hole	PS 33 CK	210130
225	40	no hole	PS 33 CK	223162
225	100	no hole	PS 33 CK	224731
150	60	hole pattern GLS51	PS 33 CK	301874
150	80	hole pattern GLS51	PS 33 CK	301925
150	100	hole pattern GLS51	PS 33 CK	301926
150	120	hole pattern GLS51	PS 33 CK	301927
225	40	hole pattern GLS52	PS 33 CK	302042
225	60	hole pattern GLS52	PS 33 CK	302043
225	80	hole pattern GLS52	PS 33 CK	302044

225	100	hole pattern GLS52	PS 33 CK	302045
225	120	hole pattern GLS52	PS 33 CK	302046
150	40	hole pattern GLS51	PS 33 CK	310531
150	60	hole pattern GLS74	PS 33 CK	340370
150	80	hole pattern GLS74	PS 33 CK	340371
150	120	hole pattern GLS74	PS 33 CK	340375
150	40	hole pattern GLS74	PS 33 CK	340853
150	100	hole pattern GLS74	PS 33 CK	342046