
Data Sheet



LS 309 X Belts with cloth backing for Metals, NF metals, Wood



Klingspor abrasive belt LS 309 X - the all-purpose abrasive belt with an outstanding price-performance ratio

The Klingspor **abrasive belt LS 309 X** is an abrasive belt for universal use in **metal and wood processing**. It sets itself apart with a great many advantages:

- Exceptional price-performance ratio
- Flexible and tear-resistant
- Optimal wear characteristics
- Highly versatile

The abrasive belt LS 309 X with its cotton backing can be combined with a wide variety of sanding machines.

Abrasive belt LS 309 X - the versatile all-purpose product

The **abrasive belt LS 309 X** boasts an X-cotton backing that is particularly **flexible and tear-resistant**. The **tear-resistant cotton backing** guarantees an exceptionally long service life. The abrasive grain is aluminium oxide, applied with a close coating and bonded with fully synthetic resin. Aluminium oxide is an abrasive that is characterised by its combination of hardness and toughness. The close coating is guaranteed to deliver aggressive abrasive performance including a high removal rate thanks to the large number of grain points. Work with superior efficiency is guaranteed. The abrasive belt is guaranteed to produce consistently flawless surface quality across a wide range of applications and workpieces. This universal product is distinguished by its optimal wear characteristics. Its superior flexibility makes the abrasive belt LS 309 X a particularly good choice for sanding contours.

Abrasive belt LS 309 X - an all-purpose product for a variety of applications

This universal product has been engineered for the needs of the metalworking industry, the wood industry and general applications in trade. It is suitable for rough and finish sanding as well as for surface sanding. The **abrasive belt LS 309 X** is ideal for use with

- pedestal sanders,
- · edge sanders and
- pipe belt sanders.

The product is geared towards use in combination with abrasive flap discs and flap wheels.

Abrasive belt LS 309 X - the product for wood and metal processing

The abrasive belt LS 309 X is a product engineered for **metal and wood processing**. It is suitable for work on wood, non-ferrous metal and metal in general. The abrasive belt LS 309 X demonstrates superior abrasive performance on all of these materials. When used for surface sanding on wood, the product produces a clean and uniform scratch pattern.

Cat.number	Type of coated abrasives	Belt joint	Grit	Length in mm	Width in mm
12875	LS 309 X	F5 glued overlapped	240	915	100
13702	LS 309 X	F5 glued overlapped	120	800	100
3683	LS 309 X	F5 glued overlapped	40	1.020	50
3692	LS 309 X	F4G butt joint	40	2.000	75
3699	LS 309 X	F5 glued overlapped	40	1.000	100
3707	LS 309 X	F4G butt joint	40	2.000	150
3732	LS 309 X	F5 glued overlapped	40	915	100
3732	LS 309 X	F5 glued overlapped	40	950	100
3807	LS 309 X	F5 glued overlapped	60	1.020	50
3819	LS 309 X	F4G butt joint	60	2.000	75
3828	LS 309 X	F5 glued overlapped	60	800	100
3830	LS 309 X	F5 glued overlapped	60	1.000	100
3842	LS 309 X	F5 glued overlapped	60	1.220	150
3846	LS 309 X	F4G butt joint	60	2.000	150
3889	LS 309 X	F5 glued overlapped	60	860	100
3889	LS 309 X	F5 glued overlapped	60	900	100
3890	LS 309 X	F5 glued overlapped	60	915	100
3890	LS 309 X	F5 glued overlapped	60	950	100
3940	LS 309 X	F5 glued overlapped	80	1.020	50
3955	LS 309 X	F4G butt joint	80	2.000	75
3965	LS 309 X	F5 glued overlapped	80	800	100
3967	LS 309 X	F5 glued overlapped	80	1.000	100
3985	LS 309 X	F5 glued overlapped	80	1.220	150
3988	LS 309 X	F4G butt joint	80	2.000	150
4042	LS 309 X	F5 glued overlapped	80	860	100
4042	LS 309 X	F5 glued overlapped	80	900	100
4043	LS 309 X	F5 glued overlapped	80	915	100
4043	LS 309 X	F5 glued overlapped	80	950	100
4083	LS 309 X	F5 glued overlapped	100	1.020	50
4101	LS 309 X	F5 glued overlapped	100	1.000	100
4162	LS 309 X	F5 glued overlapped	100	860	100
4162	LS 309 X	F5 glued overlapped	100	900	100
4162	LS 309 X	F5 glued overlapped	100	915	100
4162	LS 309 X	F5 glued overlapped	100	950	100
4202	LS 309 X	F5 glued overlapped	120	1.020	50
4219	LS 309 X	F5 glued overlapped	120	1.000	100
4267	LS 309 X	F5 glued overlapped	120	860	100
4267	LS 309 X	F5 glued overlapped	120	900	100
4268	LS 309 X	F5 glued overlapped	120	915	100
4268	LS 309 X	F5 glued overlapped	120	950	100
4305	LS 309 X	F5 glued overlapped	150	915	100
4330	LS 309 X	F5 glued overlapped	180	915	100

50	2.000	40	F4G butt joint	LS 309 X	4502
50	2.000	60	F4G butt joint	LS 309 X	4531
50	2.000	80	F4G butt joint	LS 309 X	4548