

Data Sheet



HF 100 A Carbide burs



Properties: Cylindrical burr without end-cut - Designation in accordance with DIN 8032: ZYA Advantages: For universal use - Especially suitable for surface grinding



Diameter in mm	Length in mm	Shaft diameter in mm	Height in mm	Cut	Max. RPM in rpm	structural shape	Shaft length in mm	Cat.number
3	38	3	14	double serration	100.000	cylinder without endcut	24	295482
6	50	6	18	single serration	65.000	cylinder without endcut	32	295521
6	50	6	18	double serration	65.000	cylinder without endcut	32	295531
8	64	6	19	double serration	55.000	cylinder without endcut	45	295552
9,6	64	6	19	coarse single serration	55.000	cylinder without endcut	45	295563
9,6	64	6	19	double serration	55.000	cylinder without endcut	45	295568
12,7	64	6	19	double serration	35.000	cylinder without endcut	45	295594
12,7	70	6	25	coarse single serration	35.000	cylinder without endcut	45	295604
12,7	70	6	25	double serration	35.000	cylinder without endcut	45	295609
16	70	6	25	double serration	25.000	cylinder without endcut	45	295621

6	50	6	18	Steel cut	65.000	cylinder without endcut	32	334116
6	50	6	18	Stainless steel cut	65.000	cylinder without endcut	32	334117
8	64	6	19	Steel cut	55.000	cylinder without endcut	45	334118
8	64	6	19	Stainless steel cut	55.000	cylinder without endcut	45	334119
9,6	64	6	19	Steel cut	55.000	cylinder without endcut	45	334120
9,6	64	6	19	Stainless steel cut	55.000	cylinder without endcut	45	334121
12,7	70	6	25	Steel cut	35.000	cylinder without endcut	45	334122
12,7	70	6	25	Stainless steel cut	35.000	cylinder without endcut	45	334123