

keypoint

Protecting you at work



Introduction Pack - Single Use Gloves

+353 (0) 1 885 30 30
www.keypoint-uk.co.uk





SW[®] PERFORMANCE TECHNOLOGIES

PROTECTION ON THE OUTSIDE

TouchTek[®]

SW[®] uses only the best materials in production and has developed a process that comprehensively cleanses and removes residues and processing chemicals prior to packaging. On the outside, TouchTek[®] technology reduces the contamination of sensitive materials and workspaces. On the inside, TouchTek[®] reduces the chemicals that can be absorbed through the skin, leading to irritation or painful reactions.

MilTek[®]

MilTek[®] technology delivers a more consistent thickness across the entire glove, minimizing the differences from finger to palm and from palm to cuff. SW[®] manufactures gloves to industry-leading levels of excellence, and has designed a system that incorporates protection and strength where it's needed, without adding extra bulk.

TracTek[®]

TracTek[®] technology includes a high density pattern specifically designed to maximize grip in wet or oily conditions. Optimal grip is achieved by channeling fluids effectively and maximizing surface-to-surface contact area.

PROTECTION ON THE INSIDE

DriTek[®]

SW[®]'s DriTek[®] technology is a moisture-wicking system that pulls sweat away from the skin leaving the wearer dryer, cooler and more comfortable. Not only does DriTek[®] provide a glove that is healthier and more comfortable, it also provides a glove that is easier to don and doff. This includes glove changes with recently washed or damp hands.

PROTECTION FOR THE WORLD

EcoTek[®]

A nitrile treatment that accelerates the break-down in landfills without any performance loss. Gloves with EcoTek[®] biodegrade by 92.6% in only 2 years & 6 months under test method ASTM D5526-12.

Features & Benefits

- DriTek® layer for moisture-wicking comfort & easy donning
- EcoTek® Biodegradable in Landfill to ASTM D5226-12
- MilTek® optimises thickness for durability and tactile sensitivity
- 1.5 AQL offering high-performance protection
- Multi-layer technology delivers EN Level 3 Abrasion resistance
- Fully textured grip pattern provides excellent wet & dry grip
- Skin Health Alliance Accredited
- Touchscreen compatible

Environments

- Oily and Wet Environments
- Dry Environments
- Chemical Environment

Industries

- Aerospace
- Agriculture
- Automotive
- Chemical
- DIY
- Fabrication
- Facilities
- Food
- Janitorial
- Light Assembly
- Maintenance
- Pharmaceutical
- Utilities
- Waste Management



MilTek®

DriTek®

EcoTek®



Construction	Nitrile
Colour	Black
Fingertip Thickness	0.26mm
Palm Thickness	0.22mm
Cuff Thickness	0.18mm
Length	280mm
Tensile Strength	17 MPa
Elongation	560%
Sizes	7 (S) – 12 (XXXL)
AQL	1.5
Powdered / Powder Free	Powder Free
EN 388:2003	2000
EN 388:2016	3000X
EN 374-1:2016	Type C
EN 374-5:2016	Yes
Food Approved	Yes
Gloves per Box	50
Boxes per Case	10

Features & Benefits

- TouchTek® protects skin and prevents workspace contamination
- 0.65 AQL exceeds laboratory standards
- Tested for use with chemotherapy drugs
- Fully textured surface provides excellent grip
- Silicone-free formulation prevents contamination
- Pure nitrile prevents latex allergic reaction
- Skin Health Alliance accredited

Environments

- Oily or Wet Environments
- Dry Environments

Industries

- Chemical
- Facilities
- Food
- Janitorial
- Medical (Class1 Devices)
- Painting
- Pharmaceutical
- Utilities



MilTek®

TouchTek®



Construction	Nitrile
Colour	Blue
Fingertip Thickness	0.12mm
Palm Thickness	0.10mm
Cuff Thickness	0.09mm
Length	242mm
Tensile Strength	23 MPa
Elongation	560%
Sizes	7 (S) – 11 (XXL)
AQL	0.65
Powdered / Powder Free	Powder Free
EN 374-1:2016	Type C
EN 374-5:2016	Yes
Food Approved	Yes
Gloves per Box	100
Boxes per Case	10

Powerform® S6

N20036

Features & Benefits

- TouchTek® protects skin and prevents workspace contamination
- EcoTek® Biodegradable in Landfill to ASTM D5226-12
- MilTek® optimises thickness for durability and tactile sensitivity
- 1.5 AQL offering high-performance protection
- Silicone-free formulation prevents contamination
- Beaded cuff allows for easy donning and removal
- Fully textured surface provides excellent wet and dry grip
- Skin Health Alliance Accredited
- Touchscreen compatible

Environments

- Oily and Wet Environments
- Dry Environments
- Chemical Environment

Industries

- Agriculture
- Automotive
- Chemical
- DIY
- Fabrication
- Facilities
- Food
- Garden
- Janitorial
- Light Assembly
- Packing
- Pharmaceutical
- Utilities



MilTek EcoTek TouchTek



Construction	Nitrile
Colour	Teal
Fingertip Thickness	0.15mm
Palm Thickness	0.13mm
Cuff Thickness	0.10mm
Length	242mm
Tensile Strength	21 MPa
Elongation	560%
Sizes	7 (S) – 11 (XXL)
AQL	1.5
Powdered / Powder Free	Powder Free
EN 374-1:2016	Type C
EN 374-5:2016	Yes
Food Approved	Yes
Gloves per Box	100
Boxes per Case	10

Powerform® S8+

N80771

Features & Benefits

- TracTek® high density pattern designed to maximise grip in wet or oily conditions
- Color-Q® – 2-Ply Colour construction provides durability and visual breach detection with contrasted interior colour
- TouchTek® protects skin, prevents workspace contamination
- MilTek® offers durability and tactile sensitivity
- Silicone-free formulation prevents contamination
- Skin Health Alliance accredited.

Environments

- Oily and Wet Environments
- Chemical Environment

Industries

- Automotive
- Chemical
- Engineering
- Fabrication
- Facilities
- Food
- Janitorial
- Light Assembly
- Liquid Handling
- Oil & Gas
- Painting
- Pharmaceutical
- Utilities
- Waste Management



MilTek TracTek TouchTek



Construction	2-Layer Nitrile
Colour	Green/Yellow
Fingertip Thickness	0.18mm
Palm Thickness	0.14mm
Cuff Thickness	0.11mm
Length	280mm
Tensile Strength	21 MPa
Elongation	560%
Sizes	7 (S) – 11 (XXL)
AQL	1.5
Powdered / Powder Free	Powder Free
EN 388:2016	2XX1X
EN 374-1:2016	Type C
EN 374-5:2016	Yes
Food Approved	Yes
Gloves per Box	50
Boxes per Case	10

Stellar® S6

N71688

Features & Benefits

- TouchTek® protects skin and prevents workspace contamination.
- EcoTek® Biodegradable in Landfill to ASTM D5226-12
- MilTek® optimises thickness for durability and tactile sensitivity
- 1.5 AQL offering high-performance protection
- Touchscreen compatible
- Fully textured surface provides excellent wet and dry grip
- Beaded cuff allows for easy donning and removal
- Pure nitrile prevents latex allergic reaction
- Skin Health Alliance accredited

Environments

- Oily and Wet Environments
- Chemical Environment

Industries

- Agriculture
- Automotive
- Chemical
- Cosmetics
- DIY
- Facilities
- Light Assembly
- Painting
- Pharmaceutical
- Tattooing
- Utilities



MilTek EcoTek TouchTek



Construction	Nitrile
Colour	Black
Fingertip Thickness	0.14mm
Palm Thickness	0.13mm
Cuff Thickness	0.10mm
Length	229mm
Tensile Strength	22 MPa
Elongation	540%
Sizes	7 (S) – 11 (XXL)
AQL	1.5
Powdered / Powder Free	Powder Free
EN374-1:2016	Type C
EN374-5:2016	Yes
Gloves per Box	100
Boxes per Case	10

Orange Gripper®

7181

Features & Benefits

- Tyre Tread Grip
- Chemical Resistant
- Powder Free
- Extra Thick (0.18mm)
- Nitrile Disposable
- AQL 1.5
- Touchscreen compatible

Environments

- Oily or Wet Environments
- Dry Environments

Industries

- Agriculture
- Automotive
- Chemical
- Construction
- Cosmetics
- Food
- General Fabrication
- Janitorial
- Packaging
- Painting



ORANGE GRIPPER®

Construction	Nitrile
Colour	Orange
Fingertip Thickness	0.19mm
Palm Thickness	0.20mm
Cuff Thickness	0.13mm
Length	240mm
Tensile Strength	22 MPa
Elongation	500%
Sizes	8 (M) – 11 (XXL)
AQL	1.5
Powdered / Powder Free	Powder Free
EN 374-1:2016	Type B
EN 374-5:2016	Yes
EN 388:2016	OX00A
EN 420:2003 + A1:2009	Yes
EN 455	1-2-3-4
Food Approved	Yes
Gloves per Box	100 (11(XXL) - 90)
Boxes per Case	10

Megaman[®]

EcoTek[®] Absorbent-Lined Nitrile Gloves

Product Information

Colour	Black	
Surface - Outer	Fully Textured	
Surface - Inner	DriTek [®]	
Material	Nitrile	
Grade	Powder-Free Exam	
Fit Type	Ambidextrous	
Cuff Type	Beaded	
Watertight AQL	1.5	
Finger Thickness	10.1 mil	0.26 mm
Palm Thickness	8.5 mil	0.22 mm
Cuff Thickness	7.0 mil	0.18 mm
Length	11.0"	280 mm
Weight	12.8g	



MilTek[®]
DriTek[®]
EcoTek[®]

Physical Properties

	Pre-Aging	Post-Aging
Tensile Strength	17 MPa	16 MPa
Elongation	560%	520%

Packaging

Gloves per Box	50
Boxes per Case	10

Dimensions

	Size 6 XS	Size 7 S	Size 8 M	Size 9 L	Size 10 XL	Size 11 XXL	Size 12 XXXL
Item Number	N660881	N660882	N660883	N660884	N660885	N660886	N660887
Palm Width mm	76	87	97	109	114	125	134

Standards and Certifications

Skin Health Alliance Accredited	Yes
REACH Compliant	Yes
EN 388:2016	3000X
ISO 374-1:2016	Type C
ISO 374-5:2016	Yes
EN 420:2003	Yes
CAT III Complex Design	Yes

CE 0493

CE
EN455



Supercede® X5

Nitrile Exam Gloves

Product Information

Colour	Light Blue	
Surface - Outer	Textured	
Surface - Inner	Smooth	
Material	Nitrile	
Grade	Powder-Free Exam	
Fit Type	Ambidextrous	
Cuff Type	Beaded	
Watertight AQL	0.65	
Finger Thickness	4.8 mil	0.12 mm
Palm Thickness	4.1 mil	0.10 mm
Cuff Thickness	3.5 mil	0.09 mm
Length	9.5"	242 mm
Weight	6.0g	



MilTek®
TouchTek®

Physical Properties

	Pre-Aging	Post-Aging
Tensile Strength	23 MPa	21 MPa
Elongation	560%	530%

Packaging

Gloves per Box	100
Boxes per Case	10

Dimensions

	Size 6 XS	Size 7 S	Size 8 M	Size 9 L	Size 10 XL	Size 11 XXL
Item Number	N058311	N058312	N058313	N058314	N058315	N058316
Palm Width mm	75	85	96	106	115	123

Standards and Certifications

Skin Health Alliance Accredited	Yes
REACH Compliant	Yes
ISO 374-1:2016	Type C
ISO 374-5:2016	Yes
EN 420:2003	Yes
CAT III Complex Design	Yes

CE 0493

CE
EN455

ISO 374-1:2016 / TYPE C



EN374-5:2016



Powerform[®] S6

EcoTek[®] Biodegradable Nitrile Exam Gloves

Product Information

Colour	Teal	
Surface - Outer	Fully Textured	
Surface - Inner	Smooth	
Material	Nitrile	
Grade	Powder-Free Exam	
Fit Type	Ambidextrous	
Cuff Type	Beaded	
Watertight AQL	1.5	
Finger Thickness	5.8 mil	0.15 mm
Palm Thickness	5.0 mil	0.13 mm
Cuff Thickness	3.9 mil	0.10 mm
Length	9.5"	242 mm
Weight	6.5g	



MilTek[®]
EcoTek[®]
TouchTek[®]

Physical Properties

	Pre-Aging	Post-Aging
Tensile Strength	21 MPa	20 MPa
Elongation	560%	540%

Packaging

Gloves per Box	100
Boxes per Case	10

Dimensions

	Size 7 S	Size 8 M	Size 9 L	Size 10 XL	Size 11 XXL
Item Number	N200362	N200363	N200364	N200365	N200366
Palm Width mm	89	98	108	116	125

Standards and Certifications

Skin Health Alliance Accredited	Yes
REACH Compliant	Yes
ISO 374-1:2016	Type C
ISO 374-5:2016	Yes
EN 420:2003	Yes
CAT III Complex Design	Yes

CE 0493

CE
EN455

ISO 374-1:2016/TYPE C



EN374-5:2016



EAC
TP TC 019/2011



Powerform® S8+

TracTek® High Performance Grip Nitrile Gloves

Product Information

Colour - Outer	Green/Yellow	
Surface - Outer	Fully Textured	
Surface - Inner	Smooth	
Material	Nitrile	
Grade	Powder-Free Exam	
Fit Type	Ambidextrous	
Cuff Type	Beaded	
Watertight AQL	1.5	
Finger Thickness	7.0 mil	0.18 mm
Palm Thickness	5.5 mil	0.14 mm
Cuff Thickness	4.5 mil	0.11 mm
Length	11.0"	280 mm
Weight	10.6g	



MilTek®
TracTek®
TouchTek®

Physical Properties

	Pre-Aging	Post-Aging
Tensile Strength	21 MPa	19 MPa
Elongation	560%	550%

Packaging

Gloves per Box	50
Boxes per Case	10

Dimensions

	Size 7 S	Size 8 M	Size 9 L	Size 10 XL	Size 11 XXL	Size 12 XXXL
Item Number	N807712	N807713	N807714	N807715	N807716	N807717
Palm Width mm	95	100	104	114	124	133

Standards and Certifications

Skin Health Alliance Accredited	Yes
REACH Compliant	Yes
ISO 374-1:2016	Type C
ISO 374-5:2016	Yes
EN 388:2016	2XX1X
EN 420:2003	Yes
CAT III Complex Design	Yes

CE 0493

CE
EN455



Orange Gripper®

Nitrile Tyre Tread Disposable Gloves

Product Information

Colour	Orange	
Surface - Outer	Fully Textured	
Surface - Inner	Smooth	
Material	Nitrile	
Grade	Powder-Free Exam	
Fit Type	Ambidextrous	
Cuff Type	Beaded	
Watertight AQL	1.5	
Finger Thickness	0.19 mm	
Palm Thickness	0.20 mm	
Cuff Thickness	0.13 mm	
Length	9.4"	240 mm
Weight	10.6g	



Physical Properties

	Pre-Aging	Post-Aging
Tensile Strength	22 MPa	22 MPa
Elongation	500%	400%

Packaging

Gloves per Box	100 (XXL - 90)
Boxes per Case	10

Dimensions

	Size 8 M	Size 9 L	Size 10 XL	Size 11 XXL
Item Number	7181-08	7181-09	7181-10	7181-11
Palm Width mm	95	105	115	120

Standards and Certifications

ISO 374-1:2016	Type B
ISO 374-5:2016	Yes
EN 388:2016	OX00A
EN420:2003+A1:2009	Yes
EN455-1-2-3-4	Yes



Point of Sale

FREE STANDING DISPLAY UNIT

Showcase Megaman® gloves in our easily assembled custom made FSDU! Eye catching without taking up valuable floor space. Holds 30 boxes.

COUNTER TOP DISPLAY UNIT

Showcase Megaman® gloves in our easily assembled custom made counter box, suitable for that impulse buy!



SHELF DISPLAY UNIT

Merchandise a standard size shelf with this sturdy, well branded eye catching unit. This unit holds both Megaman® vend packs and bulk boxes to suit every customers needs.



Point of Sale

FREE STANDING DISPLAY UNIT

Display your Orange Gripper merchandise on this three shelf free standing display unit.

This unit hold 30 Orange Gripper boxes.

Dimension (cm): W 53 x H 140

