

Model	Line	Standard
STELVIO	POLAR	EN ISO 20345:2011
Article	Protection	Availability in stock
88087-17L	S3 HRO HI WR SRC	AVAILABLE

Preview	Sole	PU-Rubber VIBRAM®-HRO-SRC
---------	------	---------------------------



Sole resistant to 300°C by contact. With scaff cap and compound designed with VIBRAM® for stability and grip performance. Outsole designed to strike the ground better and to improve self-cleaning. With anti-wear scaff cap.

Removable Insole



Anatomical and ergonomic removable insole with Flyfit, in direct contact with the foot, transpiring, and comfortable. The EVA HD perforated and thermoformed support ensures comfort and energy absorption.

Protection Elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.

Type	Ankle boot		
Upper	Full Grain leather Hydrotech Fabric of High Tenacity Soft Full Grain Leather		
Lining	3D Air circulation 320 gr.		
Antislip Lining	DUALMICRO		
Removable Insole	Blow-fit 2.0		
Sole	PU-Rubber VIBRAM®-HRO-SRC		
Toe Cap	C.T.C. - Composite Toe Cap		
Anti-Perforation	Zero(4K)-Antiperforation		
Size	38-48	Weight gr.	865

Working Enviroment

Building, Farming and Gardening, Mountains.

SRC (SRA+SRB)

		Sole 88 PU - RUBBER	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL ≥ 0.28	0.34	0.31
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL ≥ 0.13	0.19	0.15

Antistatic



Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Features

Symbols

S E FO A WRU P WR HRO HI SRC