

Product Data Sheet

MaxiCut® Ultra DT™ 44-3445

Colour – Coating	Black
Colour – Liner	Blue
Design	Palm coated knitwrist
Coating	NBR (Nitrile Butadiene Rubber)
Coating texture	Micro-Foam for Controlled Grip
Liner	UHMWPE-Glass-Nylon, Polyester, Spandex
Palm thickness	1.10 mm



Dimensions

Size Range	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)	Size 12 (XXXL)
Total glove length (+/-10 mm)	205	215	220	235	245	250	255
Wrist length (mm)	60	65	70	75	80	80	85
Wrist width (mm)	68	73	75	78	80	80	80
Palm width (+/-3 mm)	85	88	97	102	105	108	111
Over lock colour	Blue	Red	Orange	White	Yellow	Black	Green

EN test Results

Test	Notified Body	Result/Pass
EN 420: 2003 + A1: 2009	TÜV Rheinland	Yes
EN 388: 2016	TÜV Rheinland	4542C

If a glove due to its design and construction falls outside the scope of EN 420 in terms of hand size dimensions then this glove is classified as "fit for special purpose".



Product Data Sheet

MaxiCut® Ultra DT™ 44-3445

Typical Performance Values

EN 388:2016 A. Abrasion Resistance	> 8000 Cycles
EN 388:2016 B. Cut Resistance	> 20.0 index
EN 388:2016 C. Tear Resistance	> 75 newtons
EN 388:2016 D. Puncture Resistance	> 60 newtons
EN 388:2016 E. Cut Resistance ISO	≥ 10 Newton

HandCare®

Oeko-Tex® 100	Certified
REACH compliant	Yes
Sanitized®	Yes
Skin Health Alliance Dermatologically Accredited	Yes



Packaging

Pairs per poly bag	12
Poly bags per carton	6
Carton count	72
Carton dimensions (mm)	500 X 295 X 200



Product Data Sheet

MaxiCut® Ultra DT™ 44-3445

Weight

Size Range	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)	Size 12 (XXXL)
Glove weight / Pair (+/- 6 gram)	42	48	52	56	60	64	66
Gross Weight (Kg)	4.2	4.6	4.9	5.2	5.5	5.8	6
Carton Weight (Kg)	1	1	1	1	1	1	1
Net Weight (Kg)	3.2	3.6	3.9	4.2	4.5	4.8	5

Issue date: 09.08.2018

